

Telescoping cylinder I fully extended & outrigger beams fully extended							
 8800kg.ctwt 75% 360° (UNIT: KG)							
Working Radius (mm)	12100	16500	21000	27500	34000	40500	47000
3000	85000	55000					
3500	70000	53000	43500				
4000	61500	52000	43500				
4500	55000	49000	42000	31000			
5000	51000	46000	41000	31000			
5500	48000	44000	39000	30000			
6000	45000	41000	37000	29000	23000		
7000	37000	36000	33000	27000	22000		
8000	31000	30000	27000	24500	20000	16500	
9000	22000	24000	24000	22000	19000	15500	
10000		19700	19200	18500	17200	14500	11500
11000		16200	15900	16000	16000	13500	11000
12000		13500	13000	14600	14000	12500	10000
14000		9600	9500	10700	11500	10600	9000
16000				8000	9000	8400	8000
18000				6300	7200	7500	7000
20000				4800	5600	6000	6100
22000				3700	4500	5000	5200
24000				2800	3500	4000	4300
26000					2800	3200	3500
28000					2100	2500	2900
30000					1600	2000	2300
32000						1500	1800
34000						1100	1400
I	0	4400	8900	8900	8900	8900	8900
II	0	0	0	6500	13000	19500	26000
Reeving	12	10	8	6	5	4	3
Hook				70t			

